

Model		YHPK-06V1TBA-250L	YHPK-09V1TBA-250L	YHPK-12V1TBA-250L	
Power Supply / Refrigerant	V/Hz/Ph	220-240/50/1-R32	220-240/50/1-R32	220-240/50/1-R32	
Max Heating Capacity (1)	KW	6.5	9.2	11.6	
C.O.P (1)	W/W	4.61	4.38	4.3	
Heating Capacity Min./Max(1)	KW	3.5 / 6.5	4.3 / 9.2	5.5 / 11.6	
Heating Power Input Min./Max(1)	W	758 / 1410	927 / 2097	1107 / 2683	
C.O.P Min./Max(1)	W/W	4.5 / 4.7	4.38 / 4.71	4.3 / 4.9	
Max Heating Capacity (2)	KW	6	8.6	11.2	
C.O.P (2)	W/W	3.46	3.37	3.45	
Heating Capacity Min./Max(2)	KW	3.15 / 6	3.9 / 8.6	4.9 / 11.2	
Heating Power Input Min./Max(2)	W	943 / 1732	1162 / 2550	1401 / 3263	
C.O.P Min./Max(2)	W/W	3.34 / 3.56	3.37 / 3.58	3.3 / 3.5	
Max Cooling Capacity (3)	KW	7.45	9.5	9.8	
E.E.R (3)	W/W	4.05	4.23	3.9	
Cooling Capacity Min./Max.(3)	KW	6.22 / 7.45	6.7 / 9.5	- / 9.8	
Cooling Power Input Min./Max(3)	W	1400 / 1863	1679 / 2242	- / 2510	
E.E.R Min./Max(3)	W/W	4.05 / 4.45	4.0 / 4.6	- / 3.8	
Max Cooling Capacity (4)	KW	4.5	7.2	6.5	
E.E.R (4)	W/W	2.7	2.8	2.7	
Cooling Capacity Min./Max.(4)	KW	3.5 / 4.5	4.9 / 7.2	4.9 / 6.5	
Cooling Power Input Min./Max(4)	W	1.33 / 1.68	1451 / 2366	1358 / 2444	
E.E.R Min./Max(4)	W/W	2.5 / 2.74	2.8 / 3.1	2.6 / 3.5	
Compressor	Type-Quantity/System	Twin Rotary - 1	Twin Rotary - 1	Twin Rotary - 1	
Fan	Quantity	1	1	1	
	Airflow	m ³ /h	2500	3150	3150
	Rated power	W	34	45	45
Noise Level	Indoor/Outdoor	dB(A)	44 / 52	44 / 53	44 / 52
Water Side	Type	Plate Heat Exchanger	Plate Heat Exchanger	Plate Heat Exchanger	
Heat Exchanger	Water Pressure Drop	kPa	26	26	26
	Piping Connection	Inch	G1"	G1"	G1"
Allowable Water Flow	Min./Rated./Max	L/S	0.21 / 0.29 / 0.35	0.26 / 0.43 / 0.52	0.34 / 0.57 / 0.68
Net Dimension(LxDxH)	Indoor Unit	mm	600x650x1720	600x650x1720	600x650x1720
	Outdoor Unit	mm	1010x370x7000	1165x370x845	1165x370x845
Net Weight	Indoor Unit	Kg	139	140	140
	Outdoor Unit	Kg	57	70	77