

Model		YHPK- 06V1TBA	YHPK- 09V1TBA	YHPK- 12V1TBA	
Power Supply / Refrigerant	V/Hz/Ph	220-240/50/1-R32	220-240/50/1-R32	220-240/50/1-R32	
Max Heating Capacity (1)	KW	6.5	9.2	11.6	
C.O.P (1)	W/W	4.61	4.38	4.3	
Heating Capacity Min./Max(1)	KW	3.5 / 6.5	4.3 / 9.2	5.5 / 11.6	
Heating Power Input Min./Max(1)	W	758 / 1410	927 / 2097	1107 / 2683	
C.O.P Min./Max(1)	W/W	4.5 / 4.7	4.38 / 4.71	4.3 / 4.9	
Max Heating Capacity (2)	KW	6	8.6	11.2	
C.O.P (2)	W/W	3.46	3.37	3.45	
Heating Capacity Min./Max(2)	KW	3.15 / 6	3.9 / 8.6	4.9 / 11.2	
Heating Power Input Min./Max(2)	W	943 / 1732	1162 / 2550	1401 / 3263	
C.O.P Min./Max(2)	W/W	3.34 / 3.56	3.37 / 3.58	3.3 / 3.5	
Max Cooling Capacity (3)	KW	7.45	9.5	9.8	
E.E.R (3)	W/W	4.05	4.23	3.9	
Cooling Capacity Min./Max.(3)	KW	6.22 / 7.45	6.7 / 9.5	- / 9.8	
Cooling Power Input Min./Max(3)	W	1400 / 1863	1679 / 2242	- / 2510	
E.E.R Min./Max(3)	W/W	4.05 / 4.45	4.0 / 4.6	- / 3.8	
Max Cooling Capacity (4)	KW	4.5	7.2	6.5	
E.E.R (4)	W/W	2.7	2.8	2.7	
Cooling Capacity Min./Max.(4)	KW	3.5 / 4.5	4.9 / 7.2	4.9 / 6.5	
Cooling Power Input Min./Max(4)	W	1.33 / 1.68	1451 / 2366	1358 / 2444	
E.E.R Min./Max(4)	W/W	2.5 / 2.74	2.8 / 3.1	2.6 / 3.5	
Compressor	Type-Quantity/System	Twin Rotary - 1	Twin Rotary - 1	Twin Rotary - 1	
Fan	Quantity	1	1	1	
	Airflow	m ³ /h	2500	3150	3150
	Rated power	W	34	45	45
Noise Level	Indoor/Outdoor	dB(A)	44 / 52	44 / 53	44 / 52
Water Side	Type	Plate Heat Exchanger	Plate Heat Exchanger	Plate Heat Exchanger	
Heat Exchanger	Water Pressure Drop	kPa	26	26	26
	Piping Connection	Inch	G1"	G1"	G1"
Allowable Water Flow	Min./Rated./Max	L/S	0.21 / 0.29 / 0.35	0.26 / 0.43 / 0.52	0.34 / 0.57 / 0.68
Net Dimension(LxDxH)	Indoor Unit	mm	570x550x255	570x550x255	570x550x255
	Outdoor Unit	mm	1010x370x7000	1165x370x845	1165x370x845
Net Weight	Indoor Unit	Kg	25	25	25
	Outdoor Unit	Kg	65	78	85